



## STREETLIGHT PHOTOMETRIC TEST REPORT

NAME: LED路灯	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 130.32 lm/W			
MODEL	ZGSM-LD180KL 3M	Imax(cd)	8990	$\eta$ street_up(%)	0.0
NOMINAL POWER(W)	180	LOR(%)	100.2	$\eta$ street_down(%)	57.7
RATED VOLTAGE(V)	220	TOTAL FLUX(lm)	23457	$\eta$ house_up(%)	0.0
NOMINAL FLUX(lm)	23400	MAXIMUM @ (C, $\gamma$ )	165,70.0	$\eta$ house_down(%)	42.5
LAMPS INSIDE	1	$\eta$ up(%)	0.0	76 FLASHAREA(m2)	0.05000
TEST VOLTAGE(V)	220.1	$\eta$ down(%)	100.2	SLI	25.219


INTENSITY DISTRIBUTION DIAGRAM  
IN C PLANSMAX INTENSITY CONE SURFACE  
DISTRIBUTION DIAGRAM

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2017

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

## STREETLIGHT ISOCANDELA DIAGRAM

NAME: LED路灯	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:





## Classification:

IES:Type III - Medium  
 CIE:Average - Long  
 IES:Semi cut-off  
 CIE:Non-cut-off  
 Max.At80:143.5cd/klm  
 Max.At90:0.8820cd/klm  
 Max.80-90:143.5cd/klm

ISOCANDELA DIAGRAM	
UNIT	cd
Imax=100%	8990
90%	8091
80%	7192
70%	6293
60%	5394
50%	4495
40%	3596
30%	2697
20%	1798
10%	899
5%	450

C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:DAMIN  
 Test Date:2017

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.480m [K=1.0000]  
 Remarks:

COEFFICIENT OF UTILIZATION CURVE  
AND ISOLUX DIAGRAM

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: DAMIN  
Test Date: 2017

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.480m [K=1.0000]  
Remarks:

## ZONAL FLUX DIAGRAM

NAME: LED路灯	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:


$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	$\Phi$ lum,lamp
10	5308	5551	5661	5608	5447	5135	4982	5021	0- 10	506.9	506.9	2.16,2.17
20	5374	5830	5994	5932	5575	4978	4669	4805	10- 20	1520	2027	8.64,8.66
30	5460	6169	6241	6330	5752	4855	4376	4630	20- 30	2511	4538	19.3,19.4
40	5667	6532	6174	6732	6090	4786	3930	4473	30- 40	3463	8000	34.1,34.2
50	5957	6934	4811	7164	6540	4603	3039	4175	40- 50	4247	12247	52.2,52.3
60	6437	6507	1968	6723	7214	3780	1613	3357	50- 60	4532	16780	71.5,71.7
70	7370	3265	883.6	3241	8296	1523	863.9	1446	60- 70	4087	20867	89,89.2
80	2651	319.9	176.9	302.1	2347	254.1	142.1	264.0	70- 80	2396	23262	99.2,99.4
90	18.93	7.260	3.238	6.431	20.57	12.93	4.446	13.07	80- 90	194.8	23457	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2017

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

## ISOCANDELA DIAGRAM


NAME: LED路灯	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2017

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

## Planar Illuminance Curve




C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: DAMIN  
Test Date: 2017

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.480m [K=1.0000]  
Remarks:

LCS REPORT

NAME: LED路灯	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:

LUMINAIRE CLASSIFICATION SYSTEM(LCS) GRAPH



C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2017

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

### BUG REPORT

NAME: LED路灯	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:

#### IESNA Luminaire Flux Distribution Table:

Zone	Lumens	Luminaire %
FL - Front-Low(0-30)	2447.3	10.4
FM - Front-Medium(30-60)	7082.7	30.2
FH - Front-High(60-80)	3858.3	16.4
FVH - Front-Very High(80-90)	113.4	0.5
Total Forward Light	13502	57.6

BL - Back-Low(0-30)	2090.5	8.9
BM - Back-Medium(30-60)	5159.1	22.0
BH - Back-High(60-80)	2624.6	11.2
BVH - Back-Very High(80-90)	81.371	0.3
Total Back Light	9955.5	42.4

UL - Uplight-Low(90-100)	0	0.0
UH - Uplight-High(100-180)	0	0.0
Total Up Light	0	0.0

BUG(Back,Up,Glare) Rating	B4-U0-G4
---------------------------	----------

Zone	Downward Lumens	Upward Lumens	Total Lumens
House Side	9955.5	0	9955.5
Street Side	13502	0	13502


C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2017

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

ROAD ISOCANDELA REPORT

NAME: LED路灯	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:21cm*16cm	Shielding Angle:

ROAD SURFACE ISOCANDELA DIAGRAM



C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:DAMIN  
Test Date:2017

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.480m [K=1.0000]  
Remarks:

E:\ies文件夹\KL KM KS路灯3030 1M 2M 3M\3M\ZGSM-LD180KL 3M.GOS

